

IZJAVA O SVOJSTVIMA

(Izjava o lastnostih / Declaration of performance)

№: DoP - TI – 110H / 20- 01

u skladu s usklađenom normom EN 13163:2012+A1:2015 i
Uredbom (EU) br. 305 / 2011 koja propisuje usklađene uvjete trgovanja građevnim proizvodima
v skladu z harmoniziranim standardom EN 13163:2012+A1:2015 in
Uredbo (EU) št. 305 / 2011 o določitvi usklajenih pogojev za trženje gradbenih proizvodov
(according to EN 13163:2012+A1:2015 and Regulation (EU) No. 305/2011 laying
down harmonised conditions for the marketing of construction products)

- 1) Jedinstveni identifikacijski kod vrste proizvoda:
(Enotna identifikacijska oznaka tipa proizvoda / *Unique identification code of the product-type*)

STIROTERMAL DUO 11 (modelna godina ploče 2020)

- 2) Namjena proizvoda:
(Predvidena uporaba / *Intended use*)

Toplinsko izolacijski proizvod za zgrade

(Toplotnoizolacijski proizvod za stavbe / *Thermal insulation product for buildings*)

- 3) Proizvođač:
(Proizvajalec / *Manufacturer*)

FRAGMAT TIM d.o.o., Spodnja Rečica 77, 3270 Laško, SI

- 5) Sustav za ocjenu i provjeru svojstava (AVCP):
(Sistem ocenjevanja in preverjanja nespremenljivosti lastnosti (AVCP) / *Systems of AVCP*)

Sustav 3

(Sistem 3 / *System 3*)

- 6 a) Usklađena Norma:
(Harmoniziran standard / *Harmonized standard*)

EN 13163:2012+A1:2015

Prijavljeno tijelo:

(Priglašeni organi / *Notified body*)

ID: 0751 - FIW München, Lochhamer Schlag 4, 82166 Gräfelfing, Germany

- 7) Objavljena svojstva:
(Navedene lastnosti / *Declared performance*)

Kodna oznaka:

(Oznaka proizvoda / *Designation code*):

EPS-EN 13163-L(3)-W(3)-T(2)-S(5)-P(10)-BS250-CS(10)150-DS(N)5

Format (Format / format)

1400 mm x 800 mm x 11 mm

FRAGMAT 



ISO 9001 Q-749
ISO 14001 E-155

Bitne značajke (Bistvene značilnosti / Essential characteristics)	Svojstva (Lastnosti / Performance)				Usklađene tehničke specifikacije (Harmonizirane tehničke specifikacije / Harmonized technical specifications)
	Metode (Methode/ Methode)	Jed.mjere (Enota / unit)	Deklaracija (Deklaration / Declaration)	Tolerancija (Toleranca / Tolerance)	
Duljina (Dolžina / Length)	EN 822	[mm]	L(3)	± 3	EN 13163:2012+A1:2015
Širina (Širina / Width)	EN 822	[mm]	W(3)	± 3	
Debljina (Debelina / Thickness)	EN 823	[mm]	T(2)	± 2	
Pravokutnost (Pravokotnost / Squareness)	EN 824	[mm]	S(5)	± 5	
Ravnost (Ravnost / Flatness)	EN 825	[mm/m]	P(10)	± 10	
Čvrstoća na savijanje (Upogibna trdnost / Bending strength)	EN 12089	[kPa]	BS 250	≥ 250	
Tlačna čvrstoća (Tlačna trdnost / Compressive strength)	EN 826	[kPa]	CS(10)150	≥ 150	
Dimenzijska stabilnost (Dimenzijska stabilnost / Dimensional stability)	EN 1603	[%]	DS(N)5	± 0.5	
Reakcija na požar (Gorljivost / Reaction to fire)	EN 13501-1	[I]	E	-	
Toplinska provodljivost λ_D (toplotna prevodnost / Thermal resistance)	EN 12667	[W/mK]	0.034	-	

Debljina d_N [mm] (Debelina/Thickness)
11
0.30
Toplinski otpor R_D [m²K/W] (Toplotna upornost / Thermal resistance)

Svojstva proizvoda, navedenoga u točki 1, su u skladu s navedenim svojstvima iz točke 7. Ova izjava o svojstvima je u skladu s Uredbom (EU) br. 305 /2011 i izdaje se pod isključivom odgovornošću proizvođača, navedenog u točki 3.

(Lastnosti proizvoda, navedenega v točki 1, so v skladu z navedenimi lastnostmi iz točke 7. Za izdajo te izjave o lastnostih je v skladu z Uredbo (EU) št. 305/2011 odgovoren izključno proizvajalec, naveden v točki 3. / The performance of the product identified in point 1 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3).

Za proizvođača i u njegovo ime potpisao:

Podpisal za in v imenu proizvajalca /
Signed for and on behalf of the manufacturer)

Laško, 01.06.2020

Direktor:

(Direktor / Director)

Rok Žgajnar